



Siren is designed for alarming people when fire hazard is detected to let them evacuate. LA-D is a loop acoustic siren which can work without any external power supply. It can work on addressable loop circuits / stub circuits of AWEX FAS system only. Maximum number of devices per loop depends on: wire type, other loop elements. LA-D siren have built-in detector base which lets use this device as sounder and detector at once.

TECHNICAL DATA

FEATURE	LA-D	
TYPE	ACOUSTIC, ADDRESSABLE WITH DETECTOR BASE	
SUPPLY VOLTAGE	24 [VDC] ± 25%	
MAXIMUM SOUND LEVEL	95 [dB]	
NUMBER OF SOUND VARIANTS	32	
SYNCHRONISATION	YES	
QUIESCENT CURRENT CONSUMPTION	0,2 [mA]	
ALARM CURRENT CONSUMPTION	16 [mA]	
HOUSING IP	IP21C	
OPERATING TEMPERATURE	-25 UP TO 55 [°C]	
ADMISSIBLE RELATIVE HUMIDITY	95% AT A TEMP. 35 [°C] WITHOUT CONDENSATION	
DIMENSIONS (DIAMETER x HEIGHT)	Ø119x45 [mm]	
WEIGHT	200 [g]	
CASING COLOUR	WHITE	RED
PRODUCT CODE	FSS305	FSS312

DIMENSIONS [mm]

