

R-PI-0200-60-GO-60

Outdoor Gigabit 60W PoE Injector



Accessories


R-PMA



R-RPMA



R-CMA



Technical Specification

Networking Specifications

Gigabit Ethernet 10/100/1000Mbps (RJ45)	1
IEEE 802.3at Power over Ethernet	Support
60W bt	Support

Power Specifications

Input Voltage	100VAC ~ 240VAC 280VAC 4Hr 300VAC 1min.
Output Power	54VDC, max. 60W
Power Pin Assignment	1/2 (-), 3/6 (+); 4/5 (+), 7/8 (-)
Surge Protection Data / PoE Port	6KV
Surge Protection for AC Power	10KV

Mechanical Specifications

Dimensions (L x W x H)	255.2 x 199.9 x 90 mm
Weight	3.0 kg
LED Indicators	Power, PoE

Environmental Specifications

Weather Rating	IP67
Vandal Proof	IK10
Operating Temperature	-40°C ~ 65°C
Storage Temperature	-40°C ~ 85°C
Operating Humidity	10% ~ 90% non-condensing

Certifications

EMC	CE, FCC, VCCI, C-Tick
Safety	EN60950-1, IEC60950-1
Surge	IEC/EN 61000-4-5 Ed.2014+A1:2017